

"Black Baccara" Satin Finish foundation (F#: RB24010201)

OLP-6700 10% + OLP-9700Y 1.5%+OLP-9700R 0.2% OLP-9700B 0.03%

Phase	Trade Name	INCI Name	Supplier	Dosage (%)
	KF6038	LAURYL PEG-9 POLYDIMETHYLSILOXYETHYL DIMETHICONE		3.00
	GI34	POLYGLYCERYL-4 ISOSTEARATE		0.50
	XIAMETER PMX-0245	CYCLOPENTASILOXANE		13.50
	BENTON GEL VS-5 PCVHV	CYCLOPENTASILOXANE&DISTEARDIMONIUM HECTORITE&PROPYLENE CARBONATE		5.00
	LANOL 99	ISONONYL ISONONANOATE		3.00
	KF-96A-10CS	DIMETHICONE		7.00
A	OLP-6700	CI 77891 & BUTYL METHACRYLATE/HEMA/METHACRYLOXYETHYL PHOSPHORYLCHOLINE COPOLYMER & TRIETHOXYCAPRYLYLSILANE & ALUMINUM HYDROXIDE	OLI	10.00
		CI 77492 & BUTYL METHACRYLATE/HEMA/METHACRYLOXYETHYL PHOSPHORYLCHOLINE COPOLYMER & TRIETHOXYCAPRYLYLSILANE	OLI	1.50
		CI 77491 & BUTYL METHACRYLATE/HEMA/METHACRYLOXYETHYL PHOSPHORYLCHOLINE COPOLYMER & TRIETHOXYCAPRYLYLSILANE	OLI	0.20
		CI 77499 & BUTYL METHACRYLATE/HEMA/METHACRYLOXYETHYL PHOSPHORYLCHOLINE COPOLYMER & TRIETHOXYCAPRYLYLSILANE	OLI	0.03
		WATER	WATER	
B		GLYCERIN	GLYCERIN	4.00
		BUTYLENE GLYCOL-P	BUTYLENE GLYCOL-P	4.00
		SODIUM CHLORIDE	SODIUM CHLORIDE	0.70
		PHENOXYETHANOL	PHENOXYETHANOL	0.70

Process:

- 1 Add **Phase A** raw materials to the main pot, open the stirring and disperse evenly, heat to the target 85 °C, and keep warm
- 2 Add **Phase B** raw materials to the clean container, turn on stirring and heating, target 85 °C, stir until completely dissolved
- 3 The main pot turns on vacuum and low-speed homogenization, slowly pumps in the raw materials of **Phase B**, and after all **Phase B** is added to the main pot, turn on high-speed homogenization, and cool down after emulsification for
- 4 Homogenize at a low speed of about 40°C for 2 minutes and then discharge.

Note: The formula is for reference only, any concern regarding the formula stability & patent, test and/or verification maybe needed by your organization.